



Please fill in on the PC & enclose with the shipment!

Phone : +49 (0)821 450423-0
E-mail: registration@asg-analytik.de

To
ASG Analytik-Service GmbH

Trentiner Ring 30
D-86356 Neusäß

Sample description
<u>Urgency:</u> <input type="checkbox"/> Urgent (Attention 30% express surcharge)

Test parameters	required minimum quantity	Test method	please choose measurements
Density at 15 °C	50 ml	EN ISO 12185	<input type="checkbox"/>
Calorific value, upper	10 ml	DIN 51900-1 / -2	<input type="checkbox"/>
Flash point P.M.	150 ml	EN ISO 2719	<input type="checkbox"/>
Kinematic viscosity at 20 °C	50 ml	DIN 51562-1	<input type="checkbox"/>
Distillation characteristics	300 ml	EN ISO 3405	<input type="checkbox"/>
Cloud point	100 ml	EN 23015	<input type="checkbox"/>
CFPP	150 ml	EN 116	<input type="checkbox"/>
Carbon residue CCR (from 10 % Distillation residue)	200 ml	EN ISO 10370	<input type="checkbox"/>
Sulfur content	10 ml	EN ISO 20884 / 20846	<input type="checkbox"/>
Water content	50 ml	EN ISO 12937	<input type="checkbox"/>
Total contamination	600 ml	EN 12662	<input type="checkbox"/>
Ash content	50 ml	EN ISO 6245	<input type="checkbox"/>
Thermal stability (Sediment)	300 ml	DIN 51371	<input type="checkbox"/>
Analysis package DIN 51603-1	1000 ml		<input type="checkbox"/>



Additional test parameters	required minimum quantity	Test method	please choose measurements
Dyestuff content (Red marker)	250 ml	DIN 51430	<input type="checkbox"/>
Dyestuff content (Solvent Yellow 124)	250 ml	DIN 51430	<input type="checkbox"/>
Nitrogen content	10 ml	DIN 51444	<input type="checkbox"/>
Refractive index	20 ml	DIN 51423-2	<input type="checkbox"/>
C/H - Proportion	10 ml	ASTM D 5291	<input type="checkbox"/>
Electrical conductivity	100 ml	DIN 51412-1	<input type="checkbox"/>
Element screening	20 ml	ASG 1912	<input type="checkbox"/>
GCxGC-TOF MS	20 ml	ASG 2253	<input type="checkbox"/>
Peroxide number	50 ml	ASTM D 3703	<input type="checkbox"/>
Pourpoint	100 ml	ISO 3016	<input type="checkbox"/>
Oxygen content	1 ml	DIN 51732 mod.	<input type="checkbox"/>
Heat capacity	150 ml	ASG 2023	<input type="checkbox"/>
Thermal conductivity	100 ml	ASTM D 2717	<input type="checkbox"/>
Auto Ignition temperature	50 ml	DIN 51794	<input type="checkbox"/>

Additional parameters and remarks:

Address:

Company	:	<input type="text"/>
Contact person	:	<input type="text"/>
Street	:	<input type="text"/>
Postcode, City	:	<input type="text"/>
Phone / Fax	:	<input type="text"/>
E-mail	:	<input type="text"/>

Date

Signature